



**LCD, 4500 lumens, WXGA, 10,000:1 contrast ratio,  
Digital Link, long lamp and filter replacement cycle**

## **PT-FW530**

Price priority and easy installation LCD projector Designed to easily replace current projection installation in education and corporate environments

### **Key Features**

---

LCD, 4500 lumens, WXGA

---

Long lamp replacement cycle of 8,000 hours and filter replacement cycle of 16,000 hours.

---

Dust resistant design for lasting brightness

---

1.8x zoom lens and wide horizontal and vertical lens shift for flexible installation

---

10,000:1 contrast ratio

---





## PT-FW530

<https://eu.connect.panasonic.com/gb/en/products/projectors/pt-fw530>

<b>Power Supply</b>	AC100 - 240V 4.5 - 1.8A 50Hz/60Hz
<b>Power Consumption</b>	400W
<b>Power Consumption   Standby Mode (Eco)</b>	0.5W, 0.3W (Taiwan)
<b>Power Consumption   Standby Mode (Normal)</b>	12W
<b>Power Consumption   Standby Mode (Normal and Audio Monitor Out)</b>	30W
<b>BTU Value</b>	Max 1,365 BTU
<b>LCD Panel   Panel Size</b>	16.3 mm (0.64 in) diagonal (16:10 aspect ratio)
<b>LCD Panel   Display Method</b>	Transparent LCD panel (x 3, R/G/B)
<b>LCD Panel   Drive Method</b>	Active matrix
<b>LCD Panel   Pixels</b>	1,024,000 (1,280 x 800) x 3, total of 3,072,000 pixels
<b>Lens</b>	Manual zoom (throw ratio 1.22-2.26:1), Manual focus, F 1.6-2.2, f 17.1-31.7 mm
<b>Lamp</b>	270 W UHM lamp  Lamp replacement cycle  6,000 hours (lamp power: Normal), 8,000 hours (lamp power: Eco)  This is the maximum value when the lamp is turned on for 2 hours and off for 0.25 hours.
<b>Screen Size</b>	1.02- 7.62 m (40-300 inches) (16:10 aspect ratio)
<b>Brightness</b>	4,500 lumens  (Lamp power: Normal, Dynamic mode, Iris off, Daylight View:off, Auto Power Save:off)
<b>Center-to-Corner Uniformity</b>	90%
<b>Contrast</b>	10,000:1  (Lamp power: Normal, Dynamic mode, Iris on, Daylight View:off, Auto Power Save:off)
<b>Resolution</b>	1,280 x 800 pixels
<b>Scanning Frequency   HDMI/DIGITAL LINK</b>	fH: 15- 91 kHz, fV: 24 - 100Hz, dot clock: 25 - 162 MHz
<b>Scanning Frequency   RGB</b>	fH: 15- 91 kHz, fV: 24 - 100Hz, dot clock: 162 MHz or lower
<b>Scanning Frequency   YPBPR (YCBCR)</b>	525i (480i): fH15.73 kHz; fV59.94 Hz,  625i (576i): fH15.63 kHz; fV50 Hz,  525p (480p): fH31.47 kHz; fV60 Hz,  625p (576p): fH31.25 kHz; fV50 Hz,  750 (720)/60p: fH45.00 kHz; fV60 Hz,  750 (720)/50p: fH37.50 kHz; fV50 Hz,  1125 (1080)/60i: fH33.75 kHz; fV60 Hz,  1125 (1080)/50i: fH28.13 kHz; fV50 Hz,  1125 (1080)/25p: fH28.13 kHz; fV25 Hz,  1125 (1080)/24p: fH27.00 kHz; fV24 Hz,  1125 (1080)/24sF: fH27.00 kHz; fV48 Hz,  1125 (1080)/30p: fH33.75 kHz; fV30 Hz,  1125 (1080)/60p: fH67.50 kHz; fV60 Hz,  1125 (1080)/50p: fH56.25 kHz; fV50 Hz
<b>Scanning Frequency   Video/S-Video</b>	fH: 15.75 kHz, fV: 59.94 Hz [NTSC/NTSC4.43/PAL-M/PAL60]  fH: 15.63 kHz, fV: 50 Hz [PAL/PAL-N/SECAM]
<b>Keystone Correction Range</b>	Vertical $\pm 35^\circ$ , horizontal $\pm 35^\circ$
<b>Optical Axis Shift</b>	Vertical: $\pm 60\%$ (Manual) Horizontal: $\pm 30\%$ (Manual)
<b>Installation</b>	Ceiling/fl - or, front/rear
<b>Speaker</b>	4.0 cm (1-9/16 in) 10W (monaural) x 1
<b>Terminals   HDMI In 1/HDMI In 2   HDMI 19-Pin x2</b>	Deep Color, compatible with HDCP,  Audio signal: linear PCM  (sampling frequencies: 48 kHz, 44.1 kHz, 32 kHz)
<b>Terminals   Computer 1 In</b>	D-sub HD 15-pin (female) x 1
<b>Terminals   Computer 1 In   R, G, B</b>	0.7 Vp-p, 75 ohms, (G: 1.0 Vp-p, 75 ohms for sync on G)  H D/VD, SYNC: TTL, high impedance, positive/negative automatic

<b>Terminals   Computer 1 In   Y, PB, PR (Y, CB, CR)</b>	Y: 1.0 Vp-p (including sync signal), PBPR(CBCR): 0.7 Vp-p, 75 ohms
<b>Terminals   Computer 1 In   Y/C</b>	Y: 1.0 Vp-p (including sync signal), C: 0.286 Vp-p, 75 ohms
<b>Terminals   Computer 2 In/Computer 1 Out</b>	D-sub HD 15-pin (female) x 1
<b>Terminals   Computer 2 In/Computer 1 Out   R,G,B</b>	0.7 Vp-p, 75 ohms, (G: 1.0 Vp-p, 75 ohms for sync on G) H D/VD, SYNC: TTL, high impedance, positive/negative automatic NOTE: SYNC/HD and VD terminals do not accept tri-level sync signals.
<b>Terminals   Computer 2 In/Computer 1 Out   Y, PB, PR (Y, CB, CR)</b>	Y:1.0 Vp-p (including sync signal), PBPR(CBCR): 0.7 Vp-p, 75 ohms
<b>Terminals   Video In</b>	Pin jack x 1, 1.0 Vp-p, 75 ohms
<b>Terminals   Audio In 1/Audio In 2</b>	M3 x 2, 0.5 Vrms, input impedance: 22 kilohms or more
<b>Terminals   Audio In 3</b>	Pin jack(L, R) x 1, 0.5 Vrms, input impedance: 22 kilohms or more
<b>Terminals   Variable Audio Out</b>	M3 x 1 (monitor out, stereo)  0-2.0 Vrms, variable, output impedance: 2.2 kilohms or less
<b>Terminals   Serial In</b>	D-sub 9 p x 1, for external control (RS-232C compliant)
<b>Terminals   DIGITAL LINK/LAN</b>	RJ-45 x 1 (HDBaseT? compatible), 100Base-TX, PLink?(Class 1),  Deep Color, compatible with HDCP  A udio signal: linear PCM (sampling frequencies: 48 kHz, 44.1 kHz, 32 kHz)
<b>Terminals   LAN</b>	RJ-45 x 1 for network connection 10Base-T/100Base-TX,  compatible with Art-Net, PLink?(Class 1)
<b>Terminals   Wireless</b>	USB Type A x 1, for wireless projection with optional dongle (ET-WML100)
<b>Terminals   DC Out</b>	USB Type A x 1, for power supply (DC5 V, max 900 mA)
<b>Power Cord Length</b>	2.0 m (6 ft7 in)
<b>Cabinet Materials</b>	Molded plastic
<b>Dimensions (W x H x D)</b>	498 x 145 x 398.3mm  (19-19/32 x 5-11/16 x 15-11/16 in ) with supplied lens
<b>Weight</b>	Approx. 7.9kg (17.4lbs)
<b>Operating Noise</b>	29 dB (Eco), 33 dB (Normal)
<b>Operating Environment   Operating Temperature</b>	0-40 °C (32-104 °F)
<b>Operating Environment   Operating Humidity</b>	20%-80% (no condensation)
<b>Technology</b>	LCD