



Designed for education and corporate environments. LCD, 3 300 lumens, WXGA projector

PT-TW380

Short-throw projector for high impact presentations Designed for education and corporate environments

Key Features

LCD, 3300 lumens, WXGA

20 000 hours lamp replacement cycle in Eco mode

Projects 80 inch screen from a distance of only 80cm

Wireless projection capability (optional)

16 000: 1 contrast ratio



PT-TW380

<https://eu.connect.panasonic.com/sk/en/products/projectors/pt-tw380>

Projector type	LCD projector
LCD Panel Panel Size	15.0 mm (0.59 in) diagonal (16:10 aspect ratio)
LCD Panel Number of pixels	1,024,000 (1280 x 800 pixels) x 3
Light Source	230 W x 1 lamp
Light output	3,300 lm
Lamp replacement cycle*2	Normal: 10,000 h/Eco: 20,000 h/Quiet: 10,000 h
Filter Replacement Cycle	Normal: 5,000 h/Eco: 6,000 h/Quiet: 10,000 h
Resolution	1280 x 800 pixels
Contrast Ratio*1	20,000:1 (All white/all black, Iris: On, Image mode: Dynamic, Daylight View: Off, Lamp control: Normal)
Screen size [diagonal]	1.27–2.54 m (50–100 in), 16:10 aspect ratio
Center-to-corner zone ratio*1	85 %
Lens	Fixed zoom, manual focus lens, F = 1.8, f = 6.08 mm, throw ratio: 0.46:1 (Projection distance: 0.80 m [2.62 ft] for 80-inch image)
Keystone Correction Range	Vertical: ±15 ° (Auto, Manual), Horizontal: ±15 ° (Manual)
Installation	Ceiling/desk, front/rear
Terminals HDMI In 1/HDMI In 2	HDMI 19-pin x 2 (Compatible with HDCP 1.4, Deep Color), Audio signal: Linear PCM (Sampling frequencies: 48 kHz, 44.1 kHz, 32 kHz)
Terminals Computer 1 In	D-sub HD 15-pin (female) x 1 [RGB/YBPBR/YC]
Terminals Computer 2 In/1 Out	D-sub HD 15-pin (female) x 1 [RGB/YBPBR] (Input/output switching)
Terminals Video In	Pin jack x 1
Terminals Audio In 1	M3 (L,R) x 1
Terminals Audio In 2	Pin jack x 2 (L,R)
Terminals Audio Out	M3 (L,R) x 1 (Variable)
Terminals LAN	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, PLink™ (Class 2) compatible
Terminals Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compatible)
Terminals USB	USB Type-A (for Memory Viewer/Wireless Module [ET-WML100/AJ-WM50 series*3]/Power supply [DC 5 V/2 A])
Terminals Mini USB	x 1 (Mini-USB connector for interactive function)
Power Supply	AC 100–240 V, 50/60 Hz
Power Consumption	300 W
Built in Speaker	10 W monaural
Operation noise*1	Normal: 38 dB, Eco: 35 dB, Quiet: 30 dB
Dimensions (W x H x D)	335 x 134.1*4 x 329 mm (13 3/16" x 5 9/32"*4 x 12 15/16")
Weight*5	Approx. 3.9 kg (8.6 lbs)
Operating Environment	Operating temperature*6 : Normal use: 5–40 °C (41–104 °F) at altitudes less than 1,400 m (4,593 ft); 5–35 °C (41–95 °F) at altitudes of 1,400–2,700 m (4,593–8,858 ft); Operating humidity: 20–80 % (No condensation)
Applicable Software	Multi Monitoring & Control Software, Early Warning Software, Logo Transfer Software, Presenter Light Software (for Windows®)*7 , Wireless Projector for iOS/Android™*8 , LightPen3 Software for Windows/Mac, Whiteboard Software (for Windows)
Note	*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *2 Lamp replacement cycle stated is maximum value, at which time brightness will have decreased to 50 %. Usage environment affects lamp replacement cycle. *3 ET-WML100 Series and AJ-WM50 Series devices are both compatible with all projectors in this series, and either can be used to enable the wireless network function. *4 With legs at shortest position. *5 Average value. May differ depending on the actual unit. *6 When [LAMP POWER] is set to [NORMAL] and the projector is operated at an elevation of 1,400 m (4,593 ft) or less, if the ambient temperature exceeds 35 °C (95 °F), [LAMP POWER] will be switched to [ECO] automatically to protect the projector. When [LAMP POWER] is set to [NORMAL] and the projector is operated at an elevation between 1,400 m (4,593 ft) and 2,700 m (8,858 ft), if the ambient temperature exceeds 30 °C (86 °F), [LAMP POWER] will be switched to [ECO] automatically to protect the projector. *7 When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy, while images and sound are being transmitted. *8 When using the Wireless Projector app, display resolution differs depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800).