



## NEXT GENERATION DISPLAY WALL CONTROLLER

One box. Four outputs.  
Millions of possibilities.



### + HIGH PERFORMANCE CONTROLLER

Advancements in digital signage requirements mean that customers demand greater freedom in creating and deploying small, medium and large scale signage projects. The Datapath Fx4 is a multi-faceted stand alone display controller that supports a choice of inputs, high bandwidth loop-through as well as 4 genlocked outputs in either DisplayPort or HDMI.

The Fx4 features a DisplayPort1.2 main input alongside two HDMI1.4 inputs offering either 4k 4096x2160p at 60fps or UHD 2160p at 30fps respectively. The intuitive user interface allows users to determine which input is used.

### + FEATURES

- Infinite creative configurations
- Up to Ultra HD input, four HD 1080p outputs
- Rotates, crops, scales, mirrors and bezel corrects
- Multiple inputs for flexible connectivity (Dual HDMI1.4 or single DisplayPort1.2 inputs for 4k 60fps source capture)
- HDCP support on all inputs and outputs
- True stand-alone operation: Non-volatile configuration can adapt to changes in inputs by automatically adjusting all scale factors
- Network or USB interfaces allow platform independent control (including MAC OS X 10.6)
- Pre-load an image for use when signal is not detected

Distributor / Vertrieb:

**VIDELCO** Europe Limited – Professionelle Audio- Video- Medien-Technik  
Fon: +49 (0)2102 / 86 39-00 • Fax: +49 (0)2102 / 86 39-17 • [info@videlco.eu](mailto:info@videlco.eu) • [www.videlco.eu](http://www.videlco.eu)

## + ADDITIONAL FEATURES

Each output monitor can take its input from any region of the input image as all of the required cropping, scaling, rotation and frame-rate conversion is handled by the Fx4 hardware. These regions can overlap to allow any output to replicate another or can be configured to support any creative splice of the source material. This allows the support of many non-rectangular screen arrangements, as well as any mix of monitor orientations allowing users to create an almost unlimited multi-monitor canvas.

The Fx4 also allows users to pre-load an image for immediate display in those cases when the media source or cables malfunction and no signal is being received.

## + NETWORK CONNECTIVITY

The Datapath Fx4 has dual ethernet ports to allow users to add the device to their networks. Only one Datapath Fx4 in the chain requires connection to the physical LAN as ethernet loop through is supported on the second port, meaning multiple devices can be connected.

## + WALL DESIGNER

Datapath's hugely popular multi-screen design tool, Wall Designer has also been updated to incorporate Fx4. Wall Designer allows users to add displays from the ever expanding database of monitors, visualise their content by adding inputs and adjusting display regions and finally instantly program all Datapath Fx4s either via USB or the network ports.

## + MODELS AVAILABLE

Order Code: Datapath Fx4/H  
4k display controller w/HDCP - HDMI outputs

Order Code: Datapath Fx4/D  
4k display controller w/HDCP - DisplayPort outputs

*All products are shipped with the latest software available, unless stated otherwise. Special requirements may be organised by contacting our Sales team.*

## + SPECIFICATION

Dimensions	316 x 172 x 42mm (1.86kg)
Operating Temperature	0 - 35 °C/32 - 96 °F
Power requirements	IEC switched and fused mains connector 100-240V, 50/60Hz / 35W
Video Input Connections	DisplayPort1.2 (2160p/60 or equivalent up to 616MP/s) 2x HDMI1.4 (2160p/30 or equivalent up to 297MP/s)
Video Output connections	HDMI version: 4 x HDMI1.4 (1080p/60 or equivalent up to 165MP/s)  DisplayPort version: 4 x DP1.1 (1080p/60 or equivalent up to 165MP/s)  Loop-through (both versions): DisplayPort1.2 (locked to selected video input resolution)
Input Surface	8k x 8k maximum
Genlock Input	Analog black-burst on dedicated BNC connector. Any video input (HDMI1, HDMI2, DisplayPort)
Control Interfaces	Dual 100BaseT Ethernet ports with inbuilt managed switch. USB 2.0 Type B connector (full speed operation)
Firmware Support	Updates supported via USB and Ethernet connection
Storage	-20 to 70°C
Relative Humidity	5%-90% non-condensing
Warranty	3 years

*We are continuously developing the technology used within our product specifications are subject to change.*



Distributor / Vertrieb:

**VIDELCO** Europe Limited – Professionelle Audio- Video- Medien-Technik  
Fon: +49 (0)2102 / 86 39-00 • Fax: +49 (0)2102 / 86 39-17 • info@videlco.eu • www.videlco.eu