



***Lichtleistung des PT-MZ11KL. Stand: November 2022, basierend auf öffentlich zugänglichen Abmessungen, Gewichts- und Betriebsgeräuschwerten für LCD-Laserprojektoren mit einer Helligkeit von bis zu 20.000 lm und mehr. Messungen, Messbedingungen und Dokumentationsmethoden entsprechen den internationalen Standards unter ISO/IEC 21118:2020. Der Wert entspricht dem Durchschnitt aller Produkte beim Versand.**

PT-MZ11KL

Wir stellen den kleinsten, leichtesten und leisesten LCD-Laserprojektor seiner Klasse mit bis zu 20.000 lm*, einem kompakten 23 kg*2 (50,7 lbs) Gehäuse und einem leisen Betrieb von 42 dB*3 vor. Die optimierte optische Engine bietet eine Helligkeitssteigerung von 25 % gegenüber dem 16.000 lm*4 PT-MZ16KL bei gleicher Körpergröße und sorgt für klare Sichtbarkeit in gut beleuchteten Räumen.

Key Features

Der kleinste, leichteste und leiseste LCD-Projektor der Welt mit 11.000 lm

Mit bis zu 20.000 lm bei Wechselstrom von 100 bis 240 V, eine Weltneuheit

Langlebiger, energiesparendes Design minimiert Probleme

PT-MZ11KL

<https://eu.connect.panasonic.com/de/products/projectors/pt-mz11kl>

| Feature | Specification |
|--|---|
| Projector type | LCD projector |
| LCD Panel Panel Size | 25.4 mm (1.0 in) diagonal (16:10 aspect ratio) |
| LCD Panel Display System | Transparent LCD panel (x 3, R/G/B) |
| LCD Panel Drive Method | Active matrix method |
| LCD Panel Pixels | 2,304,000 (1920 x 1200 pixels) |
| Light Source | Laser diode |
| Light Output*1 *2 | 11,000 lm |
| Time until light output declines to 50 %*3 | 20,000 hours (NORMAL/QUIET) |
| Auflösung | WUXGA (1920 x 1200 pixels) |
| Contrast Ratio*1 | 3,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] set to [3].) |
| Screen Size (Diagonal) | 2.03–15.24 m (80–600 in), 2.54–10.16 m (100–400 in) with ET-EMU100, 2.03–12.70 m (80–500 in) with ET-EMT8004, 16:10 aspect ratio |
| Center-to-corner zone ratio*1 | 85 % |
| Lens | Optional (no lens included with this model) |
| Lens shift Vertical (from center of screen) | ±60 % (+50 %, -20 % with ET-EMU100, ±40 % with ET-EMW200, ±50 % with ET-EMW300) (powered) |
| Lens shift Horizontal (from center of screen) | ±20 % (±19 % with ET-EMW200) (powered) |
| Keystone Correction Range | Vertical: ±45 ° (±5 ° with ET-EMU100, ±14 ° with ET-EMW200/ET-EMW300, ±22 ° with ET-EMW400/ET-EMW500), Horizontal: ±40 ° (±0 ° with ET-EMU100, ±8 ° with ET-EMW200/ET-EMW300, ±15 ° with ET-EMW400/ET-EMW500). When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °. |
| Terminals SDI In | BNC x 1: 3G/HD-SDI input |
| Terminals HDMI In | HDMI 19-pin x 2 (Compatible with HDCP 2.3, Deep Color, 4K/60p signal input5), CEC supported |
| Terminals Serial/Multi Projector Sync In | D-sub 9-pin (female) x 1 for external control (RS-232C compliant) |
| Terminals Serial/Multi Projector Sync Out | D-sub 9-pin (male) x 1 for link control (RS-232C compliant) |
| Terminals REMOTE 1 | D-sub 9-pin (female) x 1 for external control (parallel) |
| Terminals Remote 2 In | M3 x 1 for wired remote control |
| Terminals Remote 2 Out | M3 x 1 for link control (for wired remote control) |
| Terminals DIGITAL LINK | RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p signal input*5) |
| Terminals LAN | RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net) |
| Terminals DC Out | USB connector (Type A) x 1 for power supply (Output: 5 V / 2 A) |
| Terminals USB | USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module, for USB memory |
| Power Supply | AC 100–240 V, 50/60 Hz |
| Power consumption*6 Maximum power consumption | 615 W (6.3–2.7 A) (630 VA) |
| Filter | Included (Estimated maintenance time: approx. 20,000 hours *7) |
| Operation noise*1 | 35 dB (NORMAL), 30 dB (QUIET) |
| Abmessung (B x H x T) | Approx. 650 x 185 x 440 mm (25 19/32" x 7 9/32" x 17 5/16") (excluding feet and protrusions), 650 x 211 x 440 mm (25 19/32" x 8 5/16" x 17 5/16") (excluding protrusions, feet at shortest position) |
| Weight*8 | Approx. 22.5 kg (49.6 lbs) |
| Operating Environment | Operating temperature: 0–45 °C (32–113 °F)*9, operating humidity: 10–80 % (no condensation) |
| Applicable Software | Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro, Projector Network Setup Software, Smart Projector Control for iOS/Android™ |

| | |
|---|---|
| Note | <p>*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *2 When [OPERATING MODE] is set to [NORMAL]. This is the value when the Zoom Lens (Model No.: ET-EMS650) is used. The value varies depending on the lens. *3 Around this time, light output will have decreased by approximately 50%. IEC62087: 2008 Broadcast contents, NORMAL Mode, [DYNAMIC CONTRAST] set to [3], under conditions with 30 °C (86 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m³ of particulate matter. Estimated time until light output decreases to 50% will vary depending on environment. *4 ET-EMT800 is compatible with PT-MZ17KL/MZ14KL/MZ11KL only. It cannot be used with PT-MZ20KL. *5 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. 4K/60p and 4K/50p signals input via DIGITAL LINK are supported in YPBPR 4:2:0 format only. *6 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). *7 Under conditions of 0.15 mg/m³ of particulate matter. Estimated maintenance time varies depending on environment. Filter can be washed and reused up to two times. *8 Average value. May differ depending on the actual unit. *9 Note that the projector cannot be used at altitudes 2,700 m (8,858 ft) or higher above sea level. In the following operating environments, light output may be reduced to protect the projector: when the projector is used at altitudes below 1,400 m (4,593 ft) and ambient temperature is 35 °C (95 °F) or higher; when the projector is used at altitudes between 1,400 m (4,593 ft) and 2,700 m (8,858 ft) exclusive and ambient temperature is 30 °C (86 °F) or higher. The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) when the optional AJ-WM50 Series Wireless Module is attached.</p> |
| Power consumption*6 On-mode power consumption (Light power) [Normal] | 540 W (AC 100–120 V), 520 W (AC 200–240 V) |
| Power consumption*6 On-mode power consumption (Light power) [Quiet] | 360 W (AC 100–120 V), 340 W (AC 200–240 V) |