



XS Series

URM III 2.6 MK2

Pro Flex XS

Product features:




Support $\pm 45^\circ$.



Minimum 1.4m diameter cylinder, only 8 cabinets.



Perfect 'S' shape.



Main Technical Specifications:

Parameter	URM III 2.6 MK2 Pro Flex XS
Pixel Pitch	2.6mm
LED Type	3-in-1 Black
Receiving card	SMD A10s Pro
Cable type	Power jumper: Neutrik True one(H07RNF standards) Signal jumper: Neutrik(Halogen Free)
Brightness	1,100 cd/m ²
Pixel Density	147,456 pixels/m ²
Pixels Per Panel	192×192 pixels
Module Size	W500mm×H125mm
Panel Size(with flightcase pins)	W500mm×H500mm×D89mm
Panel Size	W500mm×H500mm×D71mm
Weight(with flightcase pins)	8 kg/panel
Weight	7.9 kg/panel
Maintenance	Rear
Ingress Protection	IP30
Curve	(Convex) -45°~+45°(Concave)
Aspect Ratio	1:1
Panel Area	0.25 m ²
Recommended Viewing	≥2.6 m
Distance Environment	Indoor
Material	Die-cast Aluminum
Calibration	Support Brightness and Chroma
Brightness Control	Manual/Automatic
Color Temperature	2,000K~9,300K Adjustable
Horizontal Viewing Angle	160°
Vertical Viewing Angle	160°

Contrast Ratio	5,000:1
Input Power <Max>	130 W/panel
Input Power <Typical>	45 W/panel
Input Voltage	100~240 VAC
Processing Depth	16 bit
Scan Method	1/16
Refresh Rate	7,680@60 Hz
Video Frame Rate	23~240 Hz
Input Power Frequency	50~60 Hz
LED Life Time	100,000 Hours
Operating Temperature/Humidity	-10°C~+45°C/10~80%RH
Storage Temperature/Humidity	-20°C~+50°C/10~60%RH
Standard Mounting Configuration	Hanging, Stacking
Certification	FCC/IC/CE/CB/UL/UKCA/EAC

Note:

1. The image of the product above is for illustration only and may differ from the actual product (including but not limited to appearance, color, size, etc.).
2. The parameters are reference values, part of which is obtained under a specific test environment in Unilumin's internal laboratory, there may be slight differences in actual use due to differences in product batch, configuration, software versions, use conditions, and environmental factors.